



Applications

- Mid-Water Navigation Tasks
- General Observation & Situational Awareness
- Manipulator & Tooling Tasks

Goblin L Shark IP



Goblin L Shark IP Camera


Imenco's Goblin L Shark IP – Wide Angle
High Quality ultra-compact overview camera.

Overview camera with built in LED Lights

- Up to 142° Aov
- Fixed Lens
- 4500msw
Depth Rating
- Built in Led Lights

For further information, email
camera.sales.uk@imenco.com





Applications

- Mid-Water Navigation Tasks
- General Observation & Situational Awareness
- Manipulator & Tooling Tasks

Goblin L IP Camera

Technical Specifications

Performance	
Video Resolution/format	1080p@30fps
Video Format	H.264 – RTP / RTSP / UDP
Latency (Glass to Glass)	170ms
Electrical	
Power Input	24 VDC/5w (10VDC – 36VDC) or POE
Optical	
Lens	4mm to 12mm varifocal, F1.2
Light output	300 Lumens
AOV in water	3.6 Lens- 100°dia / 92° hor 2.8 Lens- 122°dia / 115° hor 1.8 Lens- 142°dia / 137° hor
Water Compensation	Dome Port -BK7
Mechanical	
Dimensions	Diameter: 74mm main Body (79mm front end) Length: 123mm (excl. connector)
Weight	In water: 0.4 Kg In air: 1.3 Kg
Housing Material	Titanium
Standard Connector	Subconn DBH13/Seacon 5506-1508
Environmental	
Operating Depth	4500 msw
Temperature	Operating: -5 to 40°C Storage: -20 to 60°C
Shock	30G peak acceleration, 25ms half sine duration, on all three axes
Vibration	10G, from 20 to 150HZ on all three axes
Electromagnetic Compatibility	BS EN 61000-6-3: 2007 Emission and BS EN 61000-6-1: 2007 Immunity

